



CALDER INDUSTRIAL MATERIALS LTD

SAFETY DATA SHEET FOR CALDERFLEX ROOF PRIMER

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: Calderflex Roof Primer **Reference:** DOCSH026 **Issue No 2:** February 2010

SUPPLIER: Calder Industrial Materials Limited
Jupiter Drive
Chester West Employment Park
Chester CH1 4EX
Tel + 44 (0) 1244 390 093
Fax + 44 (0) 1244 389 191
Emergency Telephone + 44 (0) 1244 390 093

2. COMPOSITION/INFORMATION ON INGREDIENTS:

<i>Chemical Name</i>	<i>Conc.%</i>	<i>CAS-No</i>	<i>EINECS</i>	<i>Classification</i>
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	20-30	108-65-6	203-603-9	R10 Xi; R36
2- Methoxypropyl acetate	0-0.5	70657-70-4	274-724-2	R10 Repr Cat 2; R61 Xi; R37
1,3,5-Trimethylbenzene	1-10	108-67-8	203-604-4	R10 Xi; R37 N; R51/53
Cumene	1-10	98-82-8	202-704-5	R10 Xn; R65 Xi; R37 N; R51/53
1,2,4-Trimethylbenzene	1-10	95-63-6	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53
Solvent naphtha (petroleum), light aroma	10-20	64742-95-6		R10 Xn; R65 N; R51/53 R66 R67
Chlorinated Paraffin (C14-C17)	1-10	85535-85-9	287-477-0	N; R50/53

3. HAZARDS IDENTIFICATION:

Flammable.
Irritating to eyes.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Harmful – may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES:

INHALATION: Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

INGESTION: Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. **DO NOT INDUCE VOMITING.**

SKIN CONTACT: Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

EYE CONTACT: Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: Carbon oxides.

FIRE HAZARDS: Burning produces irritating, toxic and obnoxious fumes.


PROTECTIVE EQUIPMENT: Self-contained breathing apparatus. Wear protective clothing.

6. ACCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTIONS: Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

ENVIRONMENTAL PRECAUTIONS: Do not allow product to enter drains. Prevent further spillage if safe.

CLEAN UP METHODS: Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.



CALDER INDUSTRIAL MATERIALS LTD

CALDERFLEX ROOF PRIMER

7. HANDLING AND STORAGE:

HANDLING: Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition – No smoking.

STORAGE: Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Stored in correctly labelled containers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

EXPOSURE LIMITS:	2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548
	Cumene	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250

ENGINEERING MEASURES: Ensure adequate ventilation of the working area.

RESPIRATORY PROTECTION: Wear suitable respiratory equipment when necessary.

HAND PROTECTION: Chemical resistant gloves (PVC).

EYE PROTECTION: Approved safety goggles.

PROTECTIVE EQUIPMENT: Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES:

DESCRIPTION: Liquid.

COLOUR: White.

ODOUR: Characteristic.

BOILING POINT: 145-181°C

FLASH POINT: 41°C

10. STABILITY AND REACTIVITY:

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, sparks and open flames.

MATERIALS TO AVOID: Oxidising agents.

11. TOXICOLOGICAL INFORMATION:

CORROSIVITY: Irritating to eyes.

12. ECOLOGICAL INFORMATION:

ECOTOXICITY: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS:

GENERAL INFORMATION: Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION:

ADR/RID

UN	1263	Packing Group	III
Class	3	Hazard ID	30
Proper Shipping Name	PAINT		



CALDER INDUSTRIAL MATERIALS LTD

CALDERFLEX ROOF PRIMER

14. TRANSPORT INFORMATION continued:

IMDG	UN	1263	Packing Group	III
	Class	3	Marine Pollutant	.
	EmS Code	F-E S-E		
IATA	UN	1263	Packing Group	III
	Class	3	Subsidiary Risk	-
	Packing Instruction (Cargo)	310	Maximum Quantity	220 L
	Packing Instruction (Passenger)	309	Maximum Quantity	60 L
Further information	The product is not classified as dangerous for carriage.			

15. REGULATORY INFORMATION:

LABELLING: The product is classified in accordance with 67/548/EEC.

SYMBOLS: Xn – Harmful; N – Dangerous for the environment



RISK PHRASES: R10 – Flammable.
R36 – Irritating to eyes.
R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 – Harmful: may cause lung damage if swallowed.
R67 – Vapours may cause drowsiness and dizziness.

SAFETY PHRASES: S29 – Do not empty into drains.
S62 – If swallowed, do not induce vomiting; seek medical advice immediately and show this container label.

16. OTHER INFORMATION:

Text of risk phrases in Section 2:

R10 - Flammable.
R20 – Harmful by inhalation.
R36 – Irritating to eyes.
R36/37/38 – Irritating to eyes, respiratory system and skin.
R37 – Irritating to respiratory system.
R50/53 – Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R61 – May cause harm to the unborn child.
R65 – Harmful: may cause lung damage if swallowed.
R66 – Repeated exposure may cause skin dryness or cracking.
R67 – Vapours may cause drowsiness and dizziness.

The contents of this Data sheet are not warranted to be accurate or complete and the Company can accept no liability to any customer, their employees or any other person whatsoever for any loss, injury or damage whether direct or consequential which may be caused by any error or omission from this sheet whether such error or omission is negligent or otherwise.